

# Rich Brilliant Willing

50 Greene St  
New York NY 10013  
T +1 212 388 1621  
sales@richbrilliantwilling.com



pictured: frosted interior

## Crisp

SCONCE | FLUSH MOUNT

**Year Designed**  
2015

### Description

Crisp is a simple, contemporary option for a flush-mounted light, molded from solid glass and fit for installation in the ceiling or wall and is suitable for wet locations. Its grooved front face, which brings to mind the ruffles of a potato crisp, serves to cast light over a more expansive area and add a subtle texture to interiors.

### Materials

Cast glass, anodized aluminum

**Country of Manufacture**  
Made in China

### Specification

8.5W power consumption  
550 lumens delivered

### Lamping

(1) 8.5W LED  
640 lumen source  
90 CRI

### LED Lifespan

50k hours

### Certification

ADA Compliant  
UL wet location  
AU / NZ IEC 60598  
IP rated

### Dimensions


5.25 Ø × 3.2 in Depth  
13.4 Ø × 8.2 cm Depth

### Product Weight

2.5 lb / 1.14 kg

### Packaging

(1) 3.0 lb / 1.63 kg  
7 × 7 × 7 in  
18 × 18 × 18 cm



triode<sup>3</sup> design

28, rue Jacob 75006 Paris  
+33 (0)1 43 29 40 05

contact@triodedesign.com  
www.triodedesign.com

**Model**

Crisp CR

**Variant**

white painted interior S1  
chrome S11  
frosted interior S12  
copper S13

**Color Temp**

2200K (candlelight) (TRIAC 'TR' control only) 22  
2700K (warm white) 27  
3000K (soft white) 30  
3500K (neutral white) 35

**Input Voltage**

110-120V 120  
220-240V (only with Flex "-TM" control) 220  
110-277V<sup>1</sup> 277

<sup>1</sup> Upon request. Compatible with Performance "-10" and "-DL" control.

**Control**

Standard TRIAC forward-phase (10-100% dimming) TR  
Flex 0-10V analog\* (1-100% dimming) TM  
Flex TRIAC forward-phase\* (1-100% dimming) TM  
Flex ELV reverse-phase\* (1-100% dimming) TM  
Performance 0-10V analog\* (0.1-100% dimming) 10  
Performance DALI digital\* (0.1-100% dimming) DL

\*requires external power supply

**Power**



external power supply DEX

**IP Rating**

IP20 IP20  
IP65 IP65

**Crisp**

Specification Logic



# Rich Brilliant Willing

50 Greene St  
New York NY 10013  
T +1 212 388 1621  
sales@richbrilliantwilling.com



pictured: copper metallic

## Crisp

SCONCE | FLUSH MOUNT

**Year Designed**  
2015

### Description

Crisp is a simple, contemporary option for a flush-mounted light, molded from solid glass and fit for installation in the ceiling or wall and is suitable for wet locations. Its grooved front face, which brings to mind the ruffles of a potato crisp, serves to cast light over a more expansive area and add a subtle texture to interiors.

### Materials

Cast glass, anodized aluminum

**Country of Manufacture**  
Made in China

### Specification

8.5W power consumption  
52 lumens delivered

### Lamping

(1) 8.5W LED  
640 lumen source  
90 CRI

### LED Lifespan

50k hours

### Certification

ADA Compliant  
UL wet location  
AU / NZ IEC 60598  
IP rated

### Dimensions


5.25 Ø × 3.2 in Depth  
13.4 Ø × 8.2 cm Depth

### Product Weight

2.5 lb / 1.14 kg

### Packaging

(1) 3.0 lb / 1.63 kg  
7 × 7 × 7 in  
18 × 18 × 18 cm



triode<sup>3</sup> design

28, rue Jacob 75006 Paris  
+33 (0)1 43 29 40 05

contact@triodedesign.com  
www.triodedesign.com

## Model

Crisp CR

## Variant

white painted interior S1  
chrome S11  
frosted interior S12  
copper S13

## Color Temp

2200K (candlelight) (TRIAC 'TR' control only) 22  
2700K (warm white) 27  
3000K (soft white) 30  
3500K (neutral white) 35

## Input Voltage

110-120V 120  
220-240V (only with Flex "-TM" control) 220  
110-277V<sup>1</sup> 277

<sup>1</sup> Upon request. Compatible with Performance "-10" and "-DL" control.

## Control

Standard TRIAC forward-phase (10-100% dimming) TR  
Flex 0-10V analog\* (1-100% dimming) TM  
Flex TRIAC forward-phase\* (1-100% dimming) TM  
Flex ELV reverse-phase\* (1-100% dimming) TM  
Performance 0-10V analog\* (0.1-100% dimming) 10  
Performance DALI digital\* (0.1-100% dimming) DL

\*requires external power supply

## Power

external power supply DEX


## IP Rating

IP20 IP20  
IP65 IP65

CR	-	-	-	-	-	-
model	variant	CCT	input	control	power supply	IP rating

## Crisp

Specification Logic



# Rich Brilliant Willing

50 Greene St  
New York NY 10013  
T +1 212 388 1621  
sales@richbrilliantwilling.com



pictured: chrome metallic

## Crisp

SCONCE | FLUSH MOUNT

**Year Designed**  
2015

### Description

Crisp is a simple, contemporary option for a flush-mounted light, molded from solid glass and fit for installation in the ceiling or wall and is suitable for wet locations. Its grooved front face, which brings to mind the ruffles of a potato crisp, serves to cast light over a more expansive area and add a subtle texture to interiors.

### Materials

Cast glass, anodized aluminum

**Country of Manufacture**  
Made in China

### Specification

8.5W power consumption  
106 lumens delivered

### Lamping

(1) 8.5W LED  
640 lumen source  
90 CRI

### DEX Lamping

(1) 8.5W LED  
1125 lumen source  
min 90 CRI

### LED Lifespan

50k hours

### Certification

ADA Compliant  
UL wet location  
AU / NZ IEC 60598  
IP rated

### Dimensions


5.25 Ø × 3.2 in  
13.4 Ø × 8.2 cm

### Product Weight

2.5 lb / 1.14 kg

### Packaging

(1) 3.0 lb / 1.63 kg  
7 × 7 × 7 in  
18 × 18 × 18 cm



triode<sup>3</sup> design

28, rue Jacob 75006 Paris  
+33 (0)1 43 29 40 05

contact@triodedesign.com  
www.triodedesign.com

## Model

Crisp CR

## Variant

white painted interior S1  
chrome S11  
frosted interior S12  
copper S13

## Color Temp

2200K (candlelight) (TRIAC 'TR' control only) 22  
2700K (warm white) 27  
3000K (soft white) 30  
3500K (neutral white) 35

## Input Voltage

110-120V 120  
220-240V (only with Flex "-TM" control) 220  
110-277V<sup>1</sup> 277

<sup>1</sup> Upon request. Compatible with Performance "-10" and "-DL" control.

## Control

Standard TRIAC forward-phase (10-100% dimming) TR  
Flex 0-10V analog\* (1-100% dimming) TM  
Flex TRIAC forward-phase\* (1-100% dimming) TM  
Flex ELV reverse-phase\* (1-100% dimming) TM  
Performance 0-10V analog\* (0.1-100% dimming) 10  
Performance DALI digital\* (0.1-100% dimming) DL

\*requires external power supply

## Power

external power supply DEX


## IP Rating

IP20 IP20  
IP65 IP65

CR	-	-	-	-	-	-
model	variant	CCT	input	control	power supply	IP rating

## Crisp

Specification Logic



# Rich Brilliant Willing

50 Greene St  
New York NY 10013  
T +1 212 388 1621  
sales@richbrilliantwilling.com



pictured: white painted interior

## Crisp

SCONCE | FLUSH MOUNT

**Year Designed**  
2015

### Description

Crisp is a simple, contemporary option for a flush-mounted light, molded from solid glass and fit for installation in the ceiling or wall and is suitable for wet locations. Its grooved front face, which brings to mind the ruffles of a potato crisp, serves to cast light over a more expansive area and add a subtle texture to interiors.

### Materials

Cast glass, anodized aluminum

**Country of Manufacture**  
Made in China

### Specification

8.5W power consumption  
445 lumens delivered

### Lamping

(1) 8.5W LED  
640 lumen source  
90 CRI

### LED Lifespan

50k hours

### Certification

ADA Compliant  
UL wet location  
AU / NZ IEC 60598  
IP rated

### Dimensions


5.25 Ø × 3.2 in Depth  
13.4 Ø × 8.2 cm Depth

### Product Weight

2.5 lb / 1.14 kg

### Packaging

(1) 3.0 lb / 1.63 kg  
7 × 7 × 7 in  
18 × 18 × 18 cm



triode<sup>3</sup> design

28, rue Jacob 75006 Paris  
+33 (0)1 43 29 40 05

contact@triodedesign.com  
www.triodedesign.com

**Model**

Crisp CR

**Variant**

white painted interior S1  
chrome S11  
frosted interior S12  
copper S13

**Color Temp**

2200K (candlelight) (TRIAC 'TR' control only) 22  
2700K (warm white) 27  
3000K (soft white) 30  
3500K (neutral white) 35

**Input Voltage**

110-120V 120  
220-240V (only with Flex "-TM" control) 220  
110-277V<sup>1</sup> 277

<sup>1</sup> Upon request. Compatible with Performance "-10" and "-DL" control.

**Control**

Standard TRIAC forward-phase (10-100% dimming) TR  
Flex 0-10V analog\* (1-100% dimming) TM  
Flex TRIAC forward-phase\* (1-100% dimming) TM  
Flex ELV reverse-phase\* (1-100% dimming) TM  
Performance 0-10V analog\* (0.1-100% dimming) 10  
Performance DALI digital\* (0.1-100% dimming) DL

\*requires external power supply

**Power**

external power supply DEX

**IP Rating**

IP20 IP20  
IP65 IP65

**Crisp**

Specification Logic

CR	-	-	-	-	-	-
model	variant	CCT	input	control	power supply	IP rating

