

## ABSTRACT TYPE II PVC-FREE SPECIFICATION SHEET

### PHYSICAL PROPERTIES

Total Weight:	18 oz per linear yd (480g per linear meter)
Composition:	100% TPO (Thermoplastic Olefin) face with nonwoven polyester / cellulose backing
Abrasion:	Taber Abrasion - Grade 5

### PRODUCT PACKAGING

Material Width:	54 inches; usable width 52 inches (130 cm)
Core Diameter:	3 inch ID Heavy Duty

### SPECIFICATIONS TESTING CERTIFICATION

Federal Specification:	CCC-408-D Type II Class A
WA Speciafication:	W-101 Type II Class A

### TESTING

ASTM-E84 Tunnel Test:	Class A
NFPA 286 Corner Burn Test:	Class A
EU Class Flame (EN 15102):	Passed Class B, s2
ASTM-D751 (Breaking Strength):	83 x 60
ASTM-D751 (Tear Strength):	47 x 48

PVC Free  
Phthalate Free Substrate  
Nonwoven backing is made from 50% post-consumer recycled content  
TPO face contains a minimum of 14% post-consumer recycled glass



28 rue Jacob 75006 Paris  
+33 (0)1 43 29 40 05

contact@triodedesign.com  
www.triodedesign.com