



## THIN MULTIPLES TRIAD

### SPECIFICATIONS

**Typical Lead Time**  
6-8 Weeks

**Segment Length**  
24 in [61 cm]

**Connected Sections**  
1 Section

**Mounting**  
Direct-Mount to Ceiling

**Color / Finish**  
Satin Brass

**Lens Finish**  
Frosted

**Color Temperature**  
3000K

**Power Supply**  
B. Standard Remote  
(2-Wire/TRIAC/FWD Phase,  
ELV, 0-10V)

**Canopy**  
5" Cover Plate - Remote  
Power Only

**Wattage & Lumens (per section)**  
24 IN - 20.4W, 0-1800LM  
36 IN - 28.8W, 0-2760LM

**Light Quality**  
CRI 95+, R9 90+

**LED Lifespan**  
50,000 hrs, L80

**Body Material**  
Solid Brass, PMMA

**Weight**  
24 IN - 2.7 lbs  
36 IN - 3 lbs

**Mounting**  
10ft 1/16" aircraft cable, field adjustable  
16ft Clear-jacketed 22AWG co-axial silver cord, field adjustable  
Direct-mounting and center-mounting with Linear Cable Collar options available (for up to 2 connected sections)

**Power**  
120VAC Input Voltage  
24VDC Class 2 Constant Voltage

**Certifications**  
cUL, UL, CE, Damp Location Rated, Title 24

### MORE INFORMATION & OPTIONS

**Designer**  
Peter Bristol

**Length Options**  
24 IN  
36 IN  
Connectable sections

**Color Temperature Options**  
2700K  
3000K  
3500K  
4000K

**Finish Options**  
Satin Brass  
Satin Nickel  
Black Oxide

**Dimming Options**  
2-Wire/TRIAC/Forward Phase  
0-10V  
3-Wire/Ecosystem

**Power Supply Options**  
A - Standard Local, 2-Wire/TRIAC/Forward-Phase, 0-10V, ELV  
B - Standard Remote, 2-Wire/TRIAC/Forward-Phase, 0-10V, ELV  
D - Lutron Remote, 2-Wire/TRIAC/Forward-Phase  
E - Lutron Remote, 3-Wire/Ecosystem

**Canopy Options**  
7" Local Canopy for Local Power <54W  
12.5" Local Canopy for Local Power >55W  
5" Cover Plate for Remote Power  
Remote Power Cord  
Gripper

**Optional Accessories**  
Linear Cable Collar for Center-Mounting

triode