



THIN SURFACE MOUNT DISPLAY LIGHT

SPECIFICATIONS

Typical Lead Time 6-8 Weeks	Color / Finish Satin Brass	Segment Length 24 in [61 cm]	Standoff Height 7 in [180 mm]	Connected Sections 1 Section
Lens Finish Frosted	Color Temperature 3000K	Power Supply B. Standard Remote (2-Wire/TRIAC/FWD Phase, ELV, 0-10V)	Wattage & Lumens (per segment) 24 IN – 6.8W, 0-600LM 36 IN – 9.6W, 0-920LM	Light Quality CRI 95+, R9 90+
LED Lifespan 50,000 hrs, L80	Body Material Solid Brass, PMMA	Weight 24 IN – 0.9 to 1.8 lbs 36 IN – 0.47 to 1.9 lbs	Mounting Wall brackets mount directly to surface	Power 120VAC Input Voltage 24VDC Class 2 Constant Voltage
Certifications cUL, UL, CE, Damp Location Rated, Title 24				

MORE INFORMATION & OPTIONS

Designer Peter Bristol	Length Options 24 IN 36 IN Connectable Segments	Standoff Height Options 1.75 IN (45mm) 3.5 IN (90mm) 7 IN (180mm)	Color Temperature Options 2700K 3000K 3500K 4000K	Finish Options Satin Brass Satin Nickel Black Oxide
Dimming Options 2-Wire/TRIAC/Forward Phase 0-10V 3-Wire/Ecosystem	Power Supply Options B – Standard Remote, 2-Wire/TRIAC/Forward-Phase, 0-10V, ELV D – Lutron Remote, 2-Wire/TRIAC/Forward-Phase E – Lutron Remote, 3-Wire/Ecosystem G – Plug-In Power Supply, 24VDC with in-line dimmer	Power Accessories Ground Control Toggle Switch Ground Control Dimmers Available for purchase (for shelving, counters, cabinets, etc)		

triode